



Finestre e portefinestre scorrevoli
Sliding windows

Linea Minimale
Minimal line



Linea Minimale

Minimal line

Luce e trasparenza: le linee guida del design moderno assumono caratteristiche sempre più orientate a rendere fluide le divisioni ambientali tra interno ed esterno. I sistemi integrati della Linea Minimale METRA Building garantiscono il massimo della luminosità con eccellenti performance di isolamento termico e acustico, rese ancor maggiori nei prodotti HES - High Energy Saving. I profili laterali vengono interamente nascosti, installati con soli tre centimetri nel nodo centrale.

Light and transparency: the guidelines of modern design are becoming increasingly oriented towards making the environmental divisions between interior and exterior fluid. The integrated systems of the METRA Building Minimal Line guarantee maximum brightness with excellent thermal and acoustic insulation, made even greater in HES - High Energy Saving - products. The side profiles are completely hidden, installed with only three centimetres in the central section.

NC-S 120 STH SLIM





Telaio fisso Frame	Telaio mobile Sash	Spessore vetri Glass thickness	Peso massimo anta Maximum sash weight
120 mm	45 mm o 55 mm	da 26 mm a 42 mm	400 kg
140 mm	45 mm or 55 mm	from 26 mm to 42 mm	

Trasmissione termica
Thermal transmittance

Valore Uf 3,3-4,8 W/m² K
Uf value 3,3-4,8 W/m² K

Montante centrale da 30 mm
30 mm interlock section

NC-S 175 STH HES LUX



Telaio fisso Frame	Telaio mobile Sash	Spessore vetri Glass thickness	Peso massimo anta Maximum sash weight
175 mm	68 mm	da 36 mm a 56 mm from 36 mm to 56 mm	500 kg

Montante centrale da 30 mm
30 mm interlock section

Trasmissione termica
Thermal transmittance

Valore Uf 2,45-3,25 W/m² K
Uf value 2,45-3,25 W/m² K

