



Finestre e portefinestre scorrevoli
Sliding windows

Linea Scorrevoli alzanti di grandi dimensioni
Lifting-sliding line for large dimensions

Linea Scorrevoli alzanti di grandi dimensioni




Lifting-sliding line for large dimensions

Nessun limite alla progettazione e massimo confort, con la linea Scorrevoli alzanti di grandi dimensioni METRA Building fornisce la soluzione ideale per le aperture con misure fuori standard. Sistemi in grado di garantire la massima continuità tra gli spazi interni e quelli esterni per risultati davvero d'impatto. La linea Scorrevoli alzanti di grandi dimensioni è ideata per sfruttare al massimo la luminosità e assicura elevate performance in termini di isolamento termico e acustico e di sicurezza.

No limits to design and maximum comfort, with the Large lifting sliding systems METRA Building provides the ideal solution for openings with non-standard dimensions. Systems able to guarantee maximum continuity between the indoor and outdoor spaces for truly impressive results. The Large lifting sliding systems line is designed to take maximum advantage of the brightness and ensures high performance in terms of thermal and acoustic insulation and security.

NC-S 170 STH HES

Variante tipologia / Typology variant






Telaio fisso Frame	Telaio mobile Sash	Spessore vetri Glass thickness	Peso massimo anta Maximum sash weight
170 mm	70 mm	da 23 mm a 56 mm from 23 mm to 56 mm	350 kg o 600 kg 350 kg or 600 kg

Trasmittanza termica
Thermal transmittance Valore Uf 1,6-3,4 W/m²K
Uf value 1,6-3,4 W/m²K

NC-S 150 STH HES

Variante tipologia / Typology variant




Telaio fisso Frame	Telaio mobile Sash	Spessore vetri Glass thickness	Peso massimo anta Maximum sash weight
150 mm	60 mm	da 13 mm a 46 mm from 13 mm to 46 mm	350 kg o 600 kg 350 kg or 600 kg

Trasmittanza termica
Thermal transmittance Valore Uf 2-3,3 W/m²K
Uf value 2-3,3 W/m²K

Altre soluzioni Other solutions


NC-S 120 STH



Telaio fisso Frame	Telaio mobile Sash	Spessore vetri Glass thickness	Peso massimo anta Maximum sash weight
Europa: 115 mm	45 mm	da 21 mm a 30 mm from 21 mm to 30 mm	200 kg

Trasmittanza termica
Thermal transmittance Valore Uf 2,7-3,9 W/m²K
Uf value 2,7-3,9 W/m²K

NC-S 150 I



Telaio fisso Frame	Telaio mobile Sash	Spessore vetri Glass thickness	Peso massimo anta Maximum sash weight
150 mm	60 mm	da 13 mm a 46 mm from 13 mm to 46 mm	350 kg o 600 kg 350 kg or 600 kg